

AGILE PREMIUM MG 20W40 & 20W50

Multi Grade Diesel Engine oil Exceeds API -SF/ CF

DESCRIPTION & APPLICATIONS

Multi Grade 20W40 & 20W50 is specially formulated Multi grade diesel engine oil for Trucks & Buses for excellent performance in ghat section. Exceeds API -SF/CF requirements. This oil is ideal for use in all seasons in petrol engines, naturally aspirated diesel engines operating under severe duty and supercharged diesel engines.

PERFORMANCE BENIFITS

- Excellent performances even with heavy loads.
- Made from genuine base oils.
- Ensures stable oil pressures.
- 100% Longer drain period.
- Good thermal & oxidation stability.
- Improves fuel Economy and promotes easy starting.
- Keeps the engine clean.
- Suitable for all climatic conditions.

PERFORMANCE STANDARDS MEETS

- API - SF / CF
- IS 13656: 2014
- Mack T-7/ T-8A
- US Military MIL-L-2104C

Typical Properties

Properties	Test Method	20W40	20W50
Kinematic Viscosity @100°C, cSt.	ASTM D445	13.5 - 15.5	17.5 - 19
Viscosity Index, Min.	ASTM D2270	110	120
Flash Point, (COC), °C, Min.	ASTM D92	210	220
Pour Point, °C	ASTM D97	-18	-27
Sulphated Ash, % wt., Max.	ASTM D874	1.51	1.51
TBN, mg KOH/g, Min.	ASTM D2896	8.5 - 9.5	8.5 - 9.5

*The values above are typical values. They do not constitute any contractual commitment.
Sales specifications are available on request. The present technical data sheet replaces all the previous edition.*

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request through our website www.slkkruizer.com

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

All rights reserved for Trademarks of SLK Kruizer logo and a related mark belongs to
SLK Enterprises used Under License.

Page : 2/2

SLK ENTERPRISES

R.s No: 42/1, #104-3-15, Satellite City, Morampudi, Rajahmundry, Andhra Pradesh, India 533107

Email : info@slkkruizer.com