

ULTRA TECH TDI 15W40 (API CH-4)

DESCRIPTION & APPLICATIONS

Ultra Fleet TDI 15W40 is robust engine oil, developed according to the latest oil-consumption and exhaust emission norms. It meets all current quality requirements for European, American and Japanese diesel- and gasoline oils. Ultra Fleet TDI 15W40 is especially suitable for the heavy diesel engines (trucks), but also can it be applied in gasoline, LPG- and light diesel engines, with or without turbocharger and/or catalytic converter and/or common rail. So, it is the perfect oil for a mixed fleet. Ultra Fleet TDI 15W40 fulfils the latest, strict norms concerning deposits on the piston crown, the upper piston-ring groove and the rest of the pistons. Ultra Fleet TDI 15W40 ensures both the engine and oil to stay in good condition due to the detergent dopes and the excellent oxidation inhibitors. Wear is limited to a minimum, even under the most severe circumstances, so that Ultra Fleet TDI 15W40 is guaranteed during the full drain interval. Ultra Fleet TDI 15W40 fulfil the requirements of engines complying to EURO II norms or as per vehicle manufacture recommendations where API CH 4 performance is required.

PERFORMANCE BENIFITS

- Helps reduce fuel consumption.
- Ensure a cleaner combustion.
- Excellent cold start.

PERFORMANCE STANDARD MEETS

- API - CH-4/SL/ CF-4
- MB 228.3
- VOLVO VDS-2
- ACEA E3-96

Typical Properties

Properties	Test Method	15W40 CH-4
Specific Gravity @20°C, Kg/l	ASTM D4052	0.871
Kinematic Viscosity @40°C, cSt	ASTM D445	98 - 105
Kinematic Viscosity @100°C, cSt	ASTM D445	13.5 - 15.5
Viscosity Index, Min.	ASTM D2270	> 135
Flash Point, (COC), °C, Min.	ASTM D92	220
Pour Point, °C	ASTM D97	-27
Sulphated Ash, % wt., Max.	ASTM D874	1.03
TBN, mg KOH/g, Min.	ASTM D2896	9 - 11

The values above are typical values. They do not constitute any contractual commitment. Sales specifications are available on request. The present technical data sheet replaces all the previous edition.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request through our website www.slkkruizer.com

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

All rights reserved for Trademarks of SLK Kruizer logo and a related mark belongs to
SLK Enterprises used Under License.

Page : 2/2

SLK ENTERPRISES

R.s No: 42/1, #104-3-15, Satellite City, Morampudi, Rajahmundry, Andhra Pradesh, India 533107

Email : info@slkkruizer.com