

UNITEC 15W40 CF-4

DESCRIPTION

Unitec 15W40 CF-4 Engine oil is suitable for 4-stroke gasoline and diesel engines between 1989 and 1994. It combines the following characteristics : very high resistance to oxidation, good detergent and dispersant properties; a great ability to neutralize acids and a high lubricity.

APPLICATIONS

This oil is Universal all year motor oil, intended for transport and construction. This oil is especially recommended for mixed fleets (cars and trucks). It can be used in all regions in diesel engines with natural aspiration or turbocharging and all gasoline engines

PERFORMANCE BENIFITS

- Helps reduce fuel consumption.
- Ensure a cleaner combustion.
- Excellent cold start.

PERFORMANCE STANDARD MEETS

- ALLISON C4 Level
- API CF-4/SG
- CATERPILLAR TO-2
- MAN 271
- MB 227.1
- MIL MIL-L-2104 E
- MIL MIL-L-46152 D
- VOLVO VDS level

Typical Properties

Property	Method	15W-40 CF4
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	L3.5
Relative Density @ 29.5°C	ASTM D4052	0.882
Kinematic Viscosity @ 100°C	ASTM D445	14.1
Kinematic Viscosity @ 40°C	ASTM D445	108
CCS Viscosity @ -20°C (15W)	ASTM D5293	6000
Viscosity Index	ASTM D2270	133
Pour Point	ASTM D97	-27
Flash Point, PMCC	ASTM D93	215
Sulphated Ash	ASTM D874	0.8
Total Base Number (TBN)	ASTM D2896	7.0

The values above are typical values. They do not constitute any contractual commitment. Sales specifications are available on request. The present technical data sheet replaces all the previous edition.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request through our website www.slkkruizer.com

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

All rights reserved for Trademarks of SLK Kruizer logo and a related mark belongs to SLK Enterprises used Under License.

Page : 2/2

SLK ENTERPRISES

R.s No: 42/1, #104-3-15, Satellite City, Morampudi, Rajahmundry, Andhra Pradesh, India 533107

Email : info@slkkruizer.com