

PREMIUM HD CHASSIS GREASE

CALCIUM BASED GREASE WITH HIGH TACKY ADDITIVES

DESCRIPTION

Kruizer Premium HD Chassis Grease is Calcium base grease fortified with extreme pressure additives and tackifiers for optimum performance under severe road conditions of shock loads and vibrations. These Greases are highly water repellent and surpasses all stipulated specifications

APPLICATIONS

- Kruizer Premium HD Chassis Grease is recommended for all types of chassis lubrication requirements such as ball joints, suspensions, steering gear systems, plain bearings, bushings and pins in automotive chassis assemblies
- Due to its excellent water resistance property it is ideally suited for automotive undercarriage protective coating during monsoons and wet operating conditions
- It is not recommended for high temperature application

ADVANTAGES & BENEFITS

- Excellent water resistance and good dispensing properties
- Adhesive properties provide coating to exposed parts
- Easily pumpable.

Typical Properties

Properties	Test Method	Wheel Bearing Grease
Appearance / Structure	Visual	Smooth & Homogeneous
Colour	Visual	Greenish Brown Tacky
NLGI Grade	-	2.5
Soap Type	-	Calcium
Worked Penetration @25°C , after 60 strokes , 0.1 mm units	ASTM D217	255
Drop point	ASTM D2265	95

The values above are typical values. They do not constitute any contractual commitment. Sales specifications are available on request. The present technical data sheet replaces all the previous edition.

Available Packs : 5 Kg, 18 Kg, 180 Kg

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request through our website www.slkkruizer.com

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

All rights reserved for Trademarks of SLK Kruizer logo and a related mark belongs to SLK Enterprises used Under License.

Page : 2/2

SLK ENTERPRISES

R.s No: 42/1, #104-3-15, Satellite City, Morampudi, Rajahmundry, Andhra Pradesh, India 533107

Email : info@slkkruizer.com