

ULTRA RACING PRO 5W-30 & 5W-40

Fully synthetic engine oil for passenger cars (For all types of engines)

DESCRIPTION & APPLICATIONS

Ultra Racing Pro 5W-30 & 5W40 SP are premium synthetic engine oils for ultra-low SAP and active cleansing technology for BS-VI petrol, light diesel, CNG and flex fuel engines. It provides unsurpassed sludge and wear protection. Ultra Racing Pro 5W-30 & 5W-40 SP gives superior protection in hot, extremely cold climates and severe driving conditions. It is recommended for various models of BS-VI compliant passenger cars of Tata Motors, Maruti-Suzuki, Hyundai Motors, Toyota, BMW, GM, Nissan etc. Also recommended for PHEV and HEV type electric passenger Cars & SUV's. These engine oils will further enhance performance of old BS standard vehicles where 5W-30 & 5W-40 viscosity gradient oils are recommended.

PERFORMANCE BENIFITS

- Enhanced fuel economy.
- Superior engine cleanliness and prevent sludge deposits.
- Clings to metal surfaces to make engine parts resistant to wear.
- Suitable for modern direct injection turbocharged (TGDI) engines and protection against (LSPI) low speed pre-ignition engines.
- Low SAPS technology.

PERFORMANCE STANDARD MEETS

- API SP
- ILSAC GF-6

Typical Properties

Properties	Test Method	5W-30	5W-40
Density @29.5°C	ASTM D1298	0.839	0.840
Kinematic Viscosity @100°C, cSt	ASTM D445	9.5 - 10.5	13 - 15
Kinematic Viscosity @40°C, cSt	ASTM D445	54 - 60	74 - 86
Viscosity Index, Min.	ASTM D2270	165	165
Flash Point, (COC), °C, Min.	ASTM D92	220	225
Pour Point, °C, Min.	ASTM D97	-36	-36
Sulphated Ash, % wt.	ASTM D874	≤ 0.72	≤ 0.72
Viscosity, CCS -30C (5W), mPa.s (cP)	ASTM D5293	5000 - 5600	6400 - 7000

The values above are typical values. They do not constitute any contractual commitment.
Sales specifications are available on request. The present technical data sheet replaces all the previous edition.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request through our website www.slkkruizer.com

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

All rights reserved for Trademarks of SLK Kruizer logo and a related mark belongs to
SLK Enterprises used Under License.

Page : 2/2

SLK ENTERPRISES

R.s No: 42/1, #104-3-15, Satellite City, Morampudi, Rajahmundry, Andhra Pradesh, India 533107

Email : info@slkkruizer.com